



# EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

**Certificate N°** 0075/006/161/11/21/2071

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

**Manufacturer :** JALLATTE SAS  
5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT  
France

### Description

**PPE Type :** *a safety and Personnel grounding, ESD control footwear*

**Product reference :** JALPURE SAS ESD

**Article code :** JYJY250

**Construction and material of outsole :** Polyuréthane - insert TPU

**Pictures :**



CE  
**Jallatte®**  
www.jallatte.com  
JALPURE SAS ESD JYJY250  
11/2021  
JYJY250  
EN ISO 20345 : 2011  
S3 CI SRC  
EN 61340-5-1 : 2016  
Made in Tunisia  
JALLATTE SAS  
5 Rue du Fort – Pierre Jallatte  
30170 St Hippolyte du Fort  
France  
EPI II



**Reference standard :** EN ISO 20345 : 2011 and EN 61340-5-1 : 2016

**Classification :** I **Category :** S3 CI SRC

**Size range :** 35 - 48 **Slip resistance :** SRC

**Toecap nature :** Metallic **Insert nature :** Non Metallic

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from DECEMBER 2021 and the Instruction for Use index REV. 04 - 11/2021.

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

**Issued in Lyon by**

Didier GUISSADO

Certification and Quality Manager

**Date of first issue :** 03 December 2021

**End of validity date :** 03 December 2026



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594  
Scope available on:  
www.cofrac.fr

[www.ctcgroupe.com](http://www.ctcgroupe.com)

[cemarking@ctcgroupe.com](mailto:cemarking@ctcgroupe.com)

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France  
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - [ctclyon@ctcgroupe.com](mailto:ctclyon@ctcgroupe.com)

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie  
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

**JALLATTE SAS**

# **MANUFACTURER'S TECHNICAL FILE**

**Reference of the product :** JALPURE SAS ESD

**Article code :** JYJY250

**Technical file index :** 01

**Last update :** DECEMBER, 2021

# IDENTIFICATION

Reference of the product : JALPURE SAS ESD  
Article Code : JYJY250  
Basic model  
Technical file index : 01  
Last update : DECEMBER, 2021

## Manufacturer :

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

tel : 33 (0)4.66.80.63.00

fax : 33 (0)4.66.80.63.03

## Factory :

MARTEK SARL

ROUTE DE TUNIS - ZONE INDUSTRIELLE / 7050 MENZEL BOURGUIBA

Tunisie

Tel : 00 216 72 11 37 00

JALLATTE SAS

5, rue du Fort – Pierre JALLATTE 30170 SAINT HIPPOLYTE DU FORT

France

Tel : 33 (0)4.66.80.63.00

Fax : 33 (0)4.66.80.63.03

# FOOTWEAR DESCRIPTION

## Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

The design of this footwear is: A : low shoe

## Visual description:

General view :



Outsole view :



Reference of the mould : LJ ENERGY

## Range of sizes :

35 - 48

## Construction and material of outsole :



Polyuréthane - insert TPU

## Field of use

Métiers de bouche / Hygiène - Santé / Hotellerie - Restauration

<b>Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)</b>				
		<b>Applicable</b>	<b>Covered by</b>	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.2	PPE is designed and manufactured in a way that perspiration resulting from use is minimised. Otherwise it must be equipped with means of absorbing perspiration.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.4	If it is known that the design performance of new PPE may be significantly affected by ageing, the month and year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and unambiguously marked on each item of PPE placed on the market and on its packaging.	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.6	PPE is intended for use in potentially explosive atmospheres	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.9	PPE incorporating components which can be adjusted or removed by the user	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input type="checkbox"/>	Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§2.14	Multi-risk PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.1.1	The PPE is intended to protect against impact caused by falling or ejected objects and collisions of parts of the body with an obstacle	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.1.2.1	The PPE is intended to protect against falls due to slipping	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.2	The PPE is intended to protect against static compression of a part of the body	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking
§3.7	Protection against cold	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Standard
			<input checked="" type="checkbox"/>	Instruction for use
			<input checked="" type="checkbox"/>	Marking

# FOOTWEAR CONSTITUTION

	Ref	Material	Color
UPPER	SI 00701	PUTEK PLUS BLANC FF WR FEUTRE 350 Putek plus 350 wrgore 48%PA 47% PU 5% PL CMS:147 gr:1235/1354	Blanc
	SI 00231	TISSU NON TISSE S2 BLANC tissu 80% PES 20% MTP épaisseur 1.8 hydrofuge	Blanc
COLLAR	SI 00547	ALBANY BLANC COL. 00 ACC PE Toile 225 gr/mq. Comp. PE 2/30 Kg MA 5gr/dmq	Blanc
TONGUE	SI 00060 = SI00002	Synthétique SPICE blanc synthétique épaisseur 0.70/0.75 comp. CO 45% PU 55%	Blanc
	SI 00231	TISSU NON TISSE S2 BLANC tissu 80% PES 20% MTP épaisseur 1.8 hydrofuge	Blanc
VAMP LINING	SI 00743	SURF gris ACC Toile noire doublure maille 3D 260/gr 100% PES 22gage grammage 2,5gr/dmq	noir
QUARTER LINING	SI 00568	ROMA gris 31 ACC ROV.+MTP4,5+ MGL noir MTP 80% + 20% MGL in PE épaisseur 0,5	Gris
INSOCK	TL 00155	Première de propreté grise MEMORY transfert noir Première de propreté polyuréthane 100% espansé densité 0,40	gris / noir
	951622012451XX / 9516101XXX7XXX	SECOSOL1 COMPLETE / SECOSOL2 BASE 9516A Première de propreté polyuréthane 100% et textile	Noire / Orange
OUTSOLE	CH 00116 / CH 00117	PU / PU	blanc / gris
	IN 00009	Insert semelle INFINERGY gris E-TPU Expansé thermoplastique polyuréthane densité 0,25	bleu
INSOLE	SP 00007	Première de montage conductive antiperforation antiperforation tissu aramide épaisseur 3.8/4.0 FORNITORE - FF-	blanc
TOE CAP	PU 00041	PUNTALE ALU MARTEK 522 puntale protezione 200 joules alluminio FORNITORE MARTEK	gris
INSERT	SP 00007	Première de montage conductive antiperforation antiperforation tissu aramide épaisseur 3.8/4.0 FORNITORE - FF-	blanc
DECORATIVE ELEMENTS		TALLONETTE TPU JALLATTE SUPPORT N/G	
		SERIGRAFIE JE ARGENT/GRIS AT01434	

# PROTECTION SCOPE

## Basic requirements :

This product has been designed to be a safety and Personnel grounding, ESD control - footwear footwear.

The technical rules are :

European Standard EN ISO 20344 : 2011 Personal protective equipment - test methods for footwear

European Standard EN ISO 20345 : 2011 : Personal protective equipment - Safety footwear

EN 61340-5-1 : 2016

It is a category II product

Requirement of the standard EN ISO 20345 : 2011 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol (SRC)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20345 : 2011 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (n° 1907/2006 and revisions)


## Additional requirements :

The additional requirements are :

- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Fuel oil resistance
- Upper : Water penetration and water absorption
- Penetration resistance
- Cold insulation


# MARKING - PACKAGING

## Information printed on the footwear :

- \* Logo of the Manufacturer
- \* Logo 
- \* Manufacturer's type designation
- \* Postal address of manufacturer
- \* Footwear's reference JALPURE SAS ESD
- \* Article code JYJY250
- \* Size
- \* Year of manufacture and at least quarter
- \* The number and year of the Standard used
- \* The symbol(s) of the additional requirements

## Marking example :

  
  
www.jallatte.com  
JALPURE SAS ESD JYJY250  
  
11/2021  
JYJY250  
  
EN ISO 20345 : 2011  
  
S3 CI SRC  
EN 61340-5-1 : 2016  
  
Made in Tunisia  
JALLATTE SAS  
5 Rue du Fort – Pierre Jallatte  
30170 St Hippolyte du Fort  
France  
  
EPI II



The location of marking is : Etiquette piquée à l'intérieur de la chaussure

## Method of marking on the footwear :

Etiquette CE tissu piquée sur la doublure

## Packaging :

1 paire dans une boîte chaussure

## References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	Reference	Laboratory	Reference
CTC	L210201939_2	CTC	L210611147_1
CIMAC	2017/1557-5-RP-2	CTC	L210712844_1
CIMAC	2017/1382-2-RP-2	CIMAC	2021/0646-13-RP-1
CTC	L210201913_2	CTC	L211120381_1
CTC	L210201930_1	CTC	L211120383_1
CTC	L210814749_1		

# MEANS OF CONTROL

Essais en internes mensuels : Résistance électrique ( méthode interne )- Rerforation, absorption d'énergie du talon, choc (EN ISO 20344: 2011).

Essais journaliers sur semelle : décollement bi-couche , abrasion, déchirement pantalon, flexion, dureté et densité (EN ISO 20344: 2011)

## **PPE subject to ageing :**

Peremption period : Durée maximum de 7 ans conseillée dans notice CE when stored in appropriate conditions (humidity, temperature, clean , ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

## **Declaration of conformity :**

Available on : [www.jallatte.com](http://www.jallatte.com)